

SHOCKWATCH LABEL SELECTION GUIDE

Using This Selection Guide...

This selection guide and sensor activation table should always be used as a starting point (rule of thumb). Packaging design and construction may affect the correlation between drop height and Shockwatch activation. **We recommend that you speak to a Shockwatch Representative before placing an order.**

Two things you need to know to select a Shockwatch sensitivity:

1. Cubic feet of shipment (height x width x depth)
2. Weight of shipment.

Shipment Size Weight Lbs.	0-1 CUBIC FEET	1-5 CUBIC FEET	6-15 CUBIC FEET	16-50 CUBIC FEET	50+ CUBIC FEET
0-10	GREEN	GREEN	ORANGE	ORANGE	RED
11-25	GREEN	ORANGE	ORANGE	RED	RED
26-50	ORANGE	ORANGE	RED	RED	PURPLE
51-100	ORANGE	RED	RED	PURPLE	PURPLE
101-250	RED	RED	PURPLE	PURPLE	YELLOW
*250 - 100	RED	RED	PURPLE	YELLOW	YELLOW
*1000+	—	PURPLE	YELLOW	YELLOW	YELLOW

Cubic feet = height x width x depth

EXPECTED DROP HEIGHT FOR SHOCKWATCH ACTIVATION

COLOR LABEL	YELLOW L-65	PURPLE L-55	RED L-47	ORANGE L-35	GREEN L-30
UNDER 100 LBS.	—	12-18"	12-24"	24-36"	36" - OVER
OVER 100 LBS.	6-12"	8-16"	12-18"	—	—

Metric conversions are available upon request.

*For shipments in excess of 300 pounds, you may want to consider the MAG 2000, a resettable unit that also measures direction of impact.