

Please visit www.shockwatch.com.

If you go to the following page:

http://www.shockwatch.com/shipping_handling_monitors/impact_indicator/selection_guide.php

You will find the product selection guide.

Move down the screen to this section, shown right.

This details the Shockwatch labels we currently supply, with the manufactures references.

Yellow reference: L-65

Blue reference: L-55

Red reference: L-47

Orange reference: L-35

Green reference: L-30

All these products are available from Design Packaging Group Limited.

Impact Indicator Product Specifications - Microsoft Internet Explorer

Address: http://www.shockwatch.com/shipping_handling_monitors/impact_indicator/selection_guide.php

0-10	GREEN	GREEN	ORANGE	ORANGE	RED
11-25	GREEN	ORANGE	ORANGE	RED	RED
26-50	ORANGE	ORANGE	RED	RED	PURPLE
51-100	ORANGE	RED	RED	PURPLE	PURPLE
101-250	RED	RED	PURPLE	PURPLE	YELLOW
*250 - 100	RED	RED	PURPLE	YELLOW	YELLOW
*1000+	---	PURPLE	YELLOW	YELLOW	YELLOW

Cubic feet = height x width x depth

EXPECTED DROP HEIGHT FOR SHOCKWATCH ACTIVATION					
COLOR LABEL	YELLOW L-65	PURPLE L-55	RED L-47	ORANGE L-35	GREEN L-30
UNDER 100 LBS.	---	12-18"	12-24"	24-36"	36" - OVER
OVER 100 LBS.	6-12"	8-16"	12-18"	---	---

Metric conversions are available upon request.

ShockWatch Label Selection Guide (Metric)

ShockWatch Clip, Multi-G, and Tube Selection Guide

All product is rated at 50 milliseconds

Product Name	Sensitivity	Activation Height
CX85 and CXX85 Clip & Tube Only	10G	Activates at 2" to 4" drops on hard surfaces
CX75 and CXX75 Clip & Tube Only	15G	Activates at 3" to 6" drops on hard surfaces
CX65 and CXX65 Clip & Tube Only	25G	Activates at 4" to 8" drops on hard surfaces. Most commonly used clip.
CX55 and CXX55 Clip & Tube Only	37.5G	Activates at 6" to 14" drops on hard surfaces
CX47 and CXX47 Clip & Tube Only	50G	Activates at 8" to 18" drops on hard surfaces
CX35 and CXX35 Clip & Tube Only	75G	Activation trends at 19" to 24"
CX30 and CXX30	100G	Activation trends at 24" to 10"